

VAS 6634 –

the new tyre changer
for demounting tyres without lever



- New technology for gentle tyre changing
- Safety, thanks to wdk-kit for all RFT and UHP tyres
- Optional tyre lift for easier operation

Advantages at a glance

- Automatic mounting head for tyre changing without lever
- Integrated tyre changer incl. aluminium protection and pneumatically tilting fitting column, which can also be pneumatically height-adjusted
- Pneumatic 4-claw clamp up to 30" rim width with central mounting
- Electric drive for forward and reverse action of the extra-large clamping plate
- Two rotational speeds controllable via a foot pedal
- Damage-free mounting / demounting thanks to pneumatic locking of the fitting head – with automatic rim release in the vertical and horizontal direction
- Premounted Tecnoroller for easy mounting process, incl. wdk-kit for all RFT and UHP tyres
- Optionally upgradable with tyre lift

Existing VAS 6279s can be upgraded with the automatic demounting head.

Ask your consultant.

Technical data VAS 6634

Scope of application

External rim clamping	12" to 30"
Internal rim clamping	14" to 33"
Rim width	3" to 15"
Max. wheel diameter	1,200 mm

Pneumatic unit

Max. unit force	2,500 kp
Working pressure	8 to 12 bar

Motor

Power supply (other voltages on request)	3 x 400 V, 50 Hz
Motor output	1.25 kW

Dimensions

(H x W x D) Workstation	1,950 x 1,250 x 2,000 mm
space requirements (D x W)	2,500 x 2,500 mm
Weight	278 kg
Colour	VW-grey RAL 7040

Scope of delivery

- 1 Machine VAS 6634
- 1 Set of plastic protection for clamping jaws
- 5 Sliding pieces for mounting head
- 1 Set of operating instructions

24 month guarantee for all parts.

We reserve the right to modify technical specifications and equipment. Images may contain optional extras.

Local distributor:

Beissbarth GmbH
A Bosch Group Company
Hanauer Strasse 101
80993 Muenchen (Munich, Bavaria)
Germany

Tel. +49-89-149 01-0
Fax +49-89-149 01-240

www.beissbarth.com
sales@beissbarth.com